
Data sheet R823884

Industry Cable Cat. 6, F-U/UTP, 4P, 450 MHz,black,PE,Fca,500 m



DESCRIPTION

The UV-resistant double jacket cable is suitable for outdoor use as well as for underground installation, as it is protected against longitudinal and traverse water by means of jelly.

Inner diameter after the overall sheath is removed Ø 7.2mm.

PRODUCT_IMAGE

FEATURES

- Industrial installation cables for extreme environmental conditions
- Water and oil repellent
- Suitable for indoor and outdoor installations

TECHNICAL DATA

DESCRIPTION

Cable type	Single cable
Cable design	Outdoor
Cable length	500 m
Cable application	outdoor use
Armor	Industrial-suited
Outer sheath material	PE
Cable sheath characteristics	zero-halogen
Wire type	Wire
Number of wires	8
Category	Cat. 6
Stranding	4 pairs
Wire diameter	AWG 23
Shielding	F/UTP
Cable overall diameter	Ø 10.5 mm
Protection class IP	IP 20
Packaging	Drum
Max. test frequency	450
PoE	Yes
PoE Level	4
CPR classification	Fca
MECHANICAL DATA	

VALUE / VALUE RANGE

MECHANICAL DATA

DESCRIPTION	VALUE / VALUE RANGE
-------------	---------------------

Color black

Cable Length 500.0 m / 1640 ft

ELECTRICAL DATA

DESCRIPTION VALUE / VALUE RANGE

Standard EN 50288-5-1