



# SLA-2M6000D

2M Lens Module



## Key Features

- Compatible with PNM-7000VD

## Compatible Accessories (Optional)



PNM-7000VD

# SLA-2M6000D

## 2M Lens Module



### Specifications

#### Video

Imaging Device	1/2.8" 2MP CMOS
Effective Pixels	1945(H)x1109(V)
Min. Illumination	Color: 0.055Lux(F2.0, 1/30sec) B/W: 0.055Lux(F2.0, 1/30sec)

#### Lens

Focal Length (Zoom Ratio)	6.0mm fixed focal
Max. Aperture Ratio	F2.0
Angular Field of View	H:50.4°, V:28.8°, D:58.1°
Focus Control	Fixed

#### Pan / Tilt / Rotate

Pan / Tilt / Rotate Range	-176°~+176° / 0°~65° / -90°~+90°
---------------------------	----------------------------------

#### Mechanical

Color / Material	Black / Plastic
Product dimensions / weight	Ø35.5x27.9mm, 27g

## Compatible lenses



Video	SLA-2M3600D	SLA-2M2400D	SLA-2M2800D
Imaging Device	1/2.8" 2MP CMOS	1/2.8" 2MP CMOS	1/2.8" 2MP CMOS
Effective Pixels	1945(H)x1109(V)	1945(H)x1109(V)	1945(H)x1109(V)
Min. Illumination	Color: 0.055Lux(F2.0, 1/30sec)\nB/W: 0.055Lux(F2.0, 1/30sec)	Color: 0.055Lux(F2.0, 1/30sec)\nB/W: 0.055Lux(F2.0, 1/30sec)	Color: 0.055Lux(F2.0, 1/30sec)\nB/W: 0.055Lux(F2.0, 1/30sec)
Lens	SLA-2M3600D	SLA-2M2400D	SLA-2M2800D
Focal Length (Zoom Ratio)	3.6mm fixed focal	2.4mm fixed focal	2.8mm fixed focal
Max. Aperture Ratio	F2.0	F2.0	F2.0
Angular Field of View	H:94.8°, V:49.3°, D:114.3°	H:135.4°, V:71.2°, D:161.6°	H:107.4°, V:62.2°, D:122.0°
Lens Type			
Mount Type			
Focus Control	Fixed	Fixed	Fixed
Pan / Tilt / Rotate	SLA-2M3600D	SLA-2M2400D	SLA-2M2800D
Pan / Tilt / Rotate Range	-176°~+176° / 0°~54° / -90°~+90°	-176°~+176° / 0°~30° / -90°~+90°	-176°~+176° / 0°~50° / -90°~+90°
Operational	SLA-2M3600D	SLA-2M2400D	SLA-2M2800D
Wide Dynamic Range			
Day & Night			
Mechanical	SLA-2M3600D	SLA-2M2400D	SLA-2M2800D
Color / Material	Black / Plastic	Black / Plastic	Black / Plastic
Product dimensions / weight	Ø35.5x27.9mm, 27g	Ø35.5x27.9mm, 30g	Ø35.5x27.9mm, 27g